

# SW Kenyon Matt & Semi Matt Dulling Spray

Panavision Asia Pacific

Chemwatch Hazard Alert Code: 4

Chemwatch: 40-6771

Issue Date: 18/12/2013

Version No: 2.1.1.1

Print Date: 18/12/2013

Material Safety Data Sheet according to NOHSC and ADG requirements

S.Local.AUS.EN

## SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

### Product Identifier

Product name	SW Kenyon Matt & Semi Matt Dulling Spray
Chemical Name	Not Applicable
Synonyms	Not Available
Proper shipping name	AEROSOLS
Chemical formula	Not Applicable
Other means of identification	Not Available
CAS number	Not Applicable

### Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Application is by spray atomisation from a hand held aerosol pack Use according to manufacturer's directions.
--------------------------	--

### Details of the supplier of the safety data sheet

Registered company name	Panavision Asia Pacific	SW Kenyon
Address	Unit 1, 706 Mowbray Road Lane Cove 2066 NSW Australia	PO Box 71 Cranbrook TN18 5ZR Kent United Kingdom
Telephone	+61 2 9355 2300 (9am – 5pm Monday to Friday)	+44 1580 850 770
Fax	Not Available	+44 1580 850 225
Website	Johnbarry.com.au	www.swkenyon.com
Email	Not Available	info@swkenyon.com

### Emergency telephone number

Association / Organisation	Not Available	Not Available
Emergency telephone numbers	Not Available	Not Available
Other emergency telephone numbers	Not Available	Not Available

## SECTION 2 HAZARDS IDENTIFICATION

### Classification of the substance or mixture

HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

### Label elements



Relevant risk statements are found in section 2

Poisons Schedule													
Risk Phrases <sup>[1]</sup>	<table><tr><td>R36/37</td><td>Irritating to eyes and respiratory system.</td></tr><tr><td>R66</td><td>Repeated exposure may cause skin dryness and cracking.</td></tr><tr><td>R44</td><td>Risk of explosion if heated under confinement.</td></tr><tr><td>R45(2)</td><td>May cause CANCER.</td></tr><tr><td>R67</td><td>Vapours may cause drowsiness and dizziness.</td></tr><tr><td>R12</td><td>Extremely flammable.</td></tr></table>	R36/37	Irritating to eyes and respiratory system.	R66	Repeated exposure may cause skin dryness and cracking.	R44	Risk of explosion if heated under confinement.	R45(2)	May cause CANCER.	R67	Vapours may cause drowsiness and dizziness.	R12	Extremely flammable.
R36/37	Irritating to eyes and respiratory system.												
R66	Repeated exposure may cause skin dryness and cracking.												
R44	Risk of explosion if heated under confinement.												
R45(2)	May cause CANCER.												
R67	Vapours may cause drowsiness and dizziness.												
R12	Extremely flammable.												

**Legend:** 1. Classified by Chemwatch; 2. Classification drawn from HSIS ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI

**Indication(s) of danger** F+, Xi, T

#### SAFETY ADVICE

<b>S01</b>	Keep locked up.
<b>S13</b>	Keep away from food, drink and animal feeding stuffs.
<b>S15</b>	Keep away from heat.
<b>S20</b>	When using do not eat or drink.
<b>S23</b>	Do not breathe gas/fumes/vapour/spray.
<b>S24</b>	Avoid contact with skin.
<b>S25</b>	Avoid contact with eyes.
<b>S26</b>	In case of contact with eyes, rinse with plenty of water and contact Doctor or Poisons Information Centre.
<b>S28</b>	After contact with skin, wash immediately with plenty of water
<b>S33</b>	Take precautionary measures against static discharges.
<b>S35</b>	This material and its container must be disposed of in a safe way.
<b>S38</b>	In case of insufficient ventilation, wear suitable respiratory equipment.
<b>S39</b>	Wear eye/face protection.
<b>S40</b>	To clean the floor and all objects contaminated by this material, use water and detergent.
<b>S41</b>	In case of fire and/or explosion, DO NOT BREATHE FUMES.
<b>S43</b>	In case of fire use...
<b>S45</b>	In case of accident or if you feel unwell IMMEDIATELY contact Doctor or Poisons Information Centre (show label if possible).
<b>S46</b>	If swallowed, seek medical advice immediately and show this container or label.
<b>S51</b>	Use only in well ventilated areas.
<b>S53</b>	Avoid exposure - obtain special instructions before use.
<b>S56</b>	Dispose of this material and its container at hazardous or special waste collection point.
<b>S64</b>	If swallowed, rinse mouth with water (only if the person is conscious).

#### Other hazards

	Inhalation, skin contact and/or ingestion may produce health damage*.
	Cumulative effects may result following exposure*.
	May produce skin discomfort*.

### SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

#### Substances

See section below for composition of Mixtures

#### Mixtures

CAS No	%[weight]	Name
68476-85-7.	50-75	<a href="#">LPG (liquefied petroleum gas)</a>
92062-15-2	15-45	<a href="#">naphtha petroleum, light, hydrotreated, naphthenic</a>
78-93-3	5-20	<a href="#">methyl ethyl ketone</a>
110-54-3	1-2	<a href="#">n-hexane</a>

### SECTION 4 FIRST AID MEASURES

#### Description of first aid measures

<b>Eye Contact</b>	<p>If aerosols come in contact with the eyes:</p> <ul style="list-style-type: none"><li>▶ Immediately hold the eyelids apart and flush the eye continuously for at least 15 minutes with fresh running water.</li><li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li><li>▶ Transport to hospital or doctor without delay.</li><li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li></ul>
<b>Skin Contact</b>	<p>If solids or aerosol mists are deposited upon the skin:</p> <ul style="list-style-type: none"><li>▶ Flush skin and hair with running water (and soap if available).</li><li>▶ Remove any adhering solids with industrial skin cleansing cream.</li><li>▶ <b>DO NOT use solvents.</b></li></ul>

	<ul style="list-style-type: none"> <li>▶ Seek medical attention in the event of irritation.</li> </ul>
<b>Inhalation</b>	<p>If aerosols, fumes or combustion products are inhaled:</p> <ul style="list-style-type: none"> <li>▶ Remove to fresh air.</li> <li>▶ Lay patient down. Keep warm and rested.</li> <li>▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>▶ If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>▶ Transport to hospital, or doctor.</li> </ul>
<b>Ingestion</b>	<ul style="list-style-type: none"> <li>▶ Avoid giving milk or oils.</li> <li>▶ Avoid giving alcohol.</li> <li>▶ Not considered a normal route of entry.</li> <li>▶ If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.</li> </ul>

#### Indication of any immediate medical attention and special treatment needed

	<p>For acute or short term repeated exposures to petroleum distillates or related hydrocarbons:</p> <ul style="list-style-type: none"> <li>▶ Primary threat to life, from pure petroleum distillate ingestion and/or inhalation, is respiratory failure.</li> <li>▶ Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO<sub>2</sub> 50 mm Hg) should be intubated.</li> <li>▶ Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.</li> <li>▶ A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.</li> <li>▶ Epinephrine (adrenalin) is not recommended for treatment of bronchospasm because of potential myocardial sensitisation to catecholamines. Inhaled cardioselective bronchodilators (e.g. Alupent, Salbutamol) are the preferred agents, with aminophylline a second choice.</li> <li>▶ Lavage is indicated in patients who require decontamination; ensure use of cuffed endotracheal tube in adult patients. [Ellenhorn and Barceloux: Medical Toxicology]</li> </ul> <p>Treat symptomatically. for simple ketones:</p> <p>-----</p> <p><b>BASIC TREATMENT</b></p> <p>-----</p> <ul style="list-style-type: none"> <li>▶ Establish a patent airway with suction where necessary.</li> <li>▶ Watch for signs of respiratory insufficiency and assist ventilation as necessary.</li> <li>▶ Administer oxygen by non-rebreather mask at 10 to 15 l/min.</li> <li>▶ Monitor and treat, where necessary, for pulmonary oedema .</li> <li>▶ Monitor and treat, where necessary, for shock.</li> <li>▶ <b>DO NOT use emetics.</b> Where ingestion is suspected rinse mouth and give up to 200 ml water (5mL/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.</li> <li>▶ Give activated charcoal.</li> </ul> <p>-----</p> <p><b>ADVANCED TREATMENT</b></p> <p>-----</p> <ul style="list-style-type: none"> <li>▶ Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.</li> <li>▶ Consider intubation at first sign of upper airway obstruction resulting from oedema.</li> <li>▶ Positive-pressure ventilation using a bag-valve mask might be of use.</li> <li>▶ Monitor and treat, where necessary, for arrhythmias.</li> <li>▶ Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.</li> <li>▶ Drug therapy should be considered for pulmonary oedema.</li> <li>▶ Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.</li> <li>▶ Treat seizures with diazepam.</li> <li>▶ Proparacaine hydrochloride should be used to assist eye irrigation.</li> </ul> <p>-----</p> <p><b>EMERGENCY DEPARTMENT</b></p> <p>-----</p> <ul style="list-style-type: none"> <li>▶ Laboratory analysis of complete blood count, serum electrolytes, BUN, creatinine, glucose, urinalysis, baseline for serum aminotransferases (ALT and AST), calcium, phosphorus and magnesium, may assist in establishing a treatment regime. Other useful analyses include anion and osmolar gaps, arterial blood gases (ABGs), chest radiographs and electrocardiograph.</li> <li>▶ Positive end-expiratory pressure (PEEP)-assisted ventilation may be required for acute parenchymal injury or adult respiratory distress syndrome.</li> <li>▶ Consult a toxicologist as necessary.</li> </ul> <p><i>BRONSTEIN, A.C. and CURRANCE, P.L.</i> <i>EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994</i></p>
--	---

## Extinguishing media

	<b>SMALL FIRE:</b> <ul style="list-style-type: none"><li>▶ Water spray, dry chemical or CO2</li></ul> <b>LARGE FIRE:</b> <ul style="list-style-type: none"><li>▶ Water spray or fog.</li></ul>
--	--

## Special hazards arising from the substrate or mixture

<b>Fire Incompatibility</b>	▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
-----------------------------	--

## Advice for firefighters

<b>Fire Fighting</b>	<ul style="list-style-type: none"><li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li><li>▶ May be violently or explosively reactive.</li><li>▶ Wear breathing apparatus plus protective gloves.</li><li>▶ Prevent, by any means available, spillage from entering drains or water course.</li><li>▶ If safe, switch off electrical equipment until vapour fire hazard removed.</li><li>▶ Use water delivered as a fine spray to control fire and cool adjacent area.</li><li>▶ <b>DO NOT</b> approach containers suspected to be hot.</li><li>▶ Cool fire exposed containers with water spray from a protected location.</li><li>▶ If safe to do so, remove containers from path of fire.</li></ul>
<b>Fire/Explosion Hazard</b>	<ul style="list-style-type: none"><li>▶ Liquid and vapour are highly flammable.</li><li>▶ Severe fire hazard when exposed to heat or flame.</li><li>▶ Vapour forms an explosive mixture with air.</li><li>▶ Severe explosion hazard, in the form of vapour, when exposed to flame or spark.</li><li>▶ Vapour may travel a considerable distance to source of ignition.</li><li>▶ Heating may cause expansion or decomposition with violent container rupture.</li><li>▶ Aerosol cans may explode on exposure to naked flames.</li><li>▶ Rupturing containers may rocket and scatter burning materials.</li><li>▶ Hazards may not be restricted to pressure effects.</li><li>▶ May emit acrid, poisonous or corrosive fumes.</li></ul>

## SECTION 6 ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

<b>Minor Spills</b>	<ul style="list-style-type: none"><li>▶ Clean up all spills immediately.</li><li>▶ Avoid breathing vapours and contact with skin and eyes.</li><li>▶ Wear protective clothing, impervious gloves and safety glasses.</li><li>▶ Shut off all possible sources of ignition and increase ventilation.</li><li>▶ Wipe up.</li><li>▶ If safe, damaged cans should be placed in a container outdoors, away from all ignition sources, until pressure has dissipated.</li><li>▶ Undamaged cans should be gathered and stowed safely.</li></ul>
<b>Major Spills</b>	<ul style="list-style-type: none"><li>▶ Clear area of personnel and move upwind.</li><li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li><li>▶ Wear full body protective clothing with breathing apparatus.</li><li>▶ Prevent, by all means available, spillage from entering drains or water courses.</li><li>▶ Consider evacuation (or protect in place).</li><li>▶ No smoking, naked lights or ignition sources.</li><li>▶ Increase ventilation.</li><li>▶ Stop leak if safe to do so.</li><li>▶ Water spray or fog may be used to disperse / absorb vapour.</li><li>▶ Contain or absorb spill with sand, earth or vermiculite.</li></ul>
	Personal Protective Equipment advice is contained in Section 8 of the MSDS.

## SECTION 7 HANDLING AND STORAGE

### Precautions for safe handling

<b>Safe handling</b>	<ul style="list-style-type: none"><li>▶ Avoid all personal contact, including inhalation.</li><li>▶ Wear protective clothing when risk of exposure occurs.</li><li>▶ Use in a well-ventilated area.</li><li>▶ Prevent concentration in hollows and sumps.</li><li>▶ <b>DO NOT enter confined spaces until atmosphere has been checked.</b></li><li>▶ Avoid smoking, naked lights or ignition sources.</li><li>▶ Avoid contact with incompatible materials.</li><li>▶ <b>When handling, DO NOT eat, drink or smoke.</b></li></ul>
<b>Other information</b>	<ul style="list-style-type: none"><li>▶ Store below 38 deg. C.</li><li>▶ Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may eject contents of can</li></ul>

- ▶ Store in original containers in approved flammable liquid storage area.
- ▶ **DO NOT store in pits, depressions, basements or areas where vapours may be trapped.**
- ▶ No smoking, naked lights, heat or ignition sources.
- ▶ Keep containers securely sealed. Contents under pressure.

### Conditions for safe storage, including any incompatibilities

<b>Suitable container</b>	<ul style="list-style-type: none"> <li>▶ Aerosol dispenser.</li> <li>▶ Check that containers are clearly labelled.</li> </ul>
<b>Storage incompatibility</b>	<ul style="list-style-type: none"> <li>▶ Avoid strong bases.</li> <li>▶ Compressed gases may contain a large amount of kinetic energy over and above that potentially available from the energy of reaction produced by the gas in chemical reaction with other substances</li> <li>▶ Avoid reaction with oxidising agents</li> </ul>

### PACKAGE MATERIAL INCOMPATIBILITIES

## SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

### Control parameters

#### OCCUPATIONAL EXPOSURE LIMITS (OEL)

#### INGREDIENT DATA


Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	LPG (liquefied petroleum gas)	LPG (liquified petroleum gas)	1800 (mg/m3) / 1000 (ppm)	Not Available	Not Available	Not Available
Australia Exposure Standards	methyl ethyl ketone	Methyl ethyl ketone (MEK)	445 (mg/m3) / 150 (ppm)	890 (mg/m3) / 300 (ppm)	Not Available	Not Available
Australia Exposure Standards	n-hexane	Hexane (n-Hexane)	72 (mg/m3) / 20 (ppm)	Not Available	Not Available	Not Available

#### EMERGENCY LIMITS

Ingredient	TEEL-0	TEEL-1	TEEL-2	TEEL-3
LPG (liquefied petroleum gas)	1000(ppm)	2000(ppm)	2000(ppm)	2000(ppm)
methyl ethyl ketone	200(ppm)	200(ppm)	2700(ppm)	4000(ppm)
n-hexane	50(ppm)	400(ppm)	3300(ppm)	8600(ppm)

Ingredient	Original IDLH	Revised IDLH
LPG (liquefied petroleum gas)	19,000 [LEL](ppm)	2,000 [LEL](ppm)
methyl ethyl ketone	3,000(ppm)	3,000 [Unch](ppm)
n-hexane	5,000(ppm)	1,100 [LEL](ppm)

### Exposure controls

<b>Appropriate engineering controls</b>	<p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.</p> <p>Employers may need to use multiple types of controls to prevent employee overexposure.</p> <ul style="list-style-type: none"> <li>▶ Employees exposed to confirmed human carcinogens should be authorized to do so by the employer, and work in a regulated area.</li> <li>▶ Work should be undertaken in an isolated system such as a "glove-box" .</li> </ul>
<b>Personal protection</b>	
<b>Eye and face protection</b>	<ul style="list-style-type: none"> <li>▶ Safety glasses with side shields.</li> <li>▶ Chemical goggles.</li> <li>▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as</li> </ul>

	<ul style="list-style-type: none"> <li>▶ soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]</li> </ul>
<b>Skin protection</b>	See Hand protection below
<b>Hand protection</b>	<ul style="list-style-type: none"> <li>▶ No special equipment needed when handling small quantities.</li> <li>▶ <b>OTHERWISE:</b></li> <li>▶ For potentially moderate exposures:</li> <li>▶ Wear general protective gloves, eg. light weight rubber gloves.</li> <li>▶ For potentially heavy exposures:</li> <li>▶ Wear chemical protective gloves, eg. PVC. and safety footwear.</li> </ul>
<b>Body protection</b>	See Other protection below
<b>Other protection</b>	<ul style="list-style-type: none"> <li>▶ Employees working with confirmed human carcinogens should be provided with, and be required to wear, clean, full body protective clothing (smocks, coveralls, or long-sleeved shirt and pants), shoe covers and gloves prior to entering the regulated area. [AS/NZS ISO 6529:2006 or national equivalent]</li> <li>▶ Employees engaged in handling operations involving carcinogens should be provided with, and required to wear and use half-face filter-type respirators with filters for dusts, mists and fumes, or air purifying canisters or cartridges. A respirator affording higher levels of protection may be substituted. [AS/NZS 1715 or national equivalent]</li> <li>▶ Emergency deluge showers and eyewash fountains, supplied with potable water, should be located near, within sight of, and on the same level with locations where direct exposure is likely.</li> <li>▶ Prior to each exit from an area containing confirmed human carcinogens, employees should be required to remove and leave protective clothing and equipment at the point of exit and at the last exit of the day, to place used clothing and equipment in impervious containers at the point of exit for purposes of decontamination or disposal. The contents of such impervious containers must be identified with suitable labels. For maintenance and decontamination activities, authorized employees entering the area should be provided with and required to wear clean, impervious garments, including gloves, boots and continuous-air supplied hood.</li> <li>▶ Prior to removing protective garments the employee should undergo decontamination and be required to shower upon removal of the garments and hood.</li> </ul>
<b>Thermal hazards</b>	

## Recommended material(s)

### GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

**"Forsberg Clothing Performance Index".**

The effect(s) of the following substance(s) are taken into account in the

**computer-generated** selection:

SW Kenyon Matt & Semi Matt Dulling Spray

Material	CPI
BUTYL	A
PE/EVAL/PE	A
TEFLON	A
BUTYL/NEOPRENE	B
PVA	B

\* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

**NOTE:** As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

## Respiratory protection

Type EAX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant.

Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Required minimum protection factor	Maximum gas/vapour concentration present in air p.p.m. (by volume)	Half-face Respirator	Full-Face Respirator
up to 10	1000	EAX-AUS / Class1	-
up to 50	1000	-	EAX-AUS / Class 1
up to 50	5000	Airline *	-
up to 100	5000	-	EAX-2
up to 100	10000	-	EAX-3
100+			Airline**

\* - Continuous Flow \*\* - Continuous-flow or positive pressure demand  
A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

## SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Appearance</b>	Aerosol product.		
<b>Physical state</b>	Compressed Gas	<b>Relative density (Water = 1)</b>	Not Available
<b>Odour</b>	Not Available	<b>Partition coefficient n-octanol / water</b>	Not Available

<b>Odour threshold</b>	Not Available	<b>Auto-ignition temperature (°C)</b>	Not Available
<b>pH (as supplied)</b>	Not Available	<b>Decomposition temperature</b>	Not Available
<b>Melting point / freezing point (°C)</b>	Not Available	<b>Viscosity (cSt)</b>	Not Available
<b>Initial boiling point and boiling range (°C)</b>	Not Available	<b>Molecular weight (g/mol)</b>	Not Applicable
<b>Flash point (°C)</b>	Not Available	<b>Taste</b>	Not Available
<b>Evaporation rate</b>	Not Available	<b>Explosive properties</b>	Not Available
<b>Flammability</b>	Not Available	<b>Oxidising properties</b>	Not Available
<b>Upper Explosive Limit (%)</b>	Not Available	<b>Surface Tension (dyn/cm or mN/m)</b>	Not Available
<b>Lower Explosive Limit (%)</b>	Not Available	<b>Volatile Component (%vol)</b>	Not Available
<b>Vapour pressure (kPa)</b>	Not Available	<b>Gas group</b>	Not Available
<b>Solubility in water (g/L)</b>	Not Available	<b>pH as a solution(1%)</b>	Not Available
<b>Vapour density (Air = 1)</b>	Not Available		

## SECTION 10 STABILITY AND REACTIVITY

<b>Reactivity</b>	See section 7
<b>Chemical stability</b>	<ul style="list-style-type: none"> <li>▶ Elevated temperatures.</li> <li>▶ Presence of open flame.</li> <li>▶ Product is considered stable.</li> <li>▶ Hazardous polymerisation will not occur.</li> <li>▶ Presence of heat source</li> <li>▶ Presence of an ignition source</li> </ul>
<b>Possibility of hazardous reactions</b>	See section 7
<b>Conditions to avoid</b>	See section 7
<b>Incompatible materials</b>	See section 7
<b>Hazardous decomposition products</b>	See section 5

## SECTION 11 TOXICOLOGICAL INFORMATION

### Information on toxicological effects

<b>Inhaled</b>	<p>Evidence shows, or practical experience predicts, that the material produces irritation of the respiratory system, in a substantial number of individuals, following inhalation. In contrast to most organs, the lung is able to respond to a chemical insult by first removing or neutralising the irritant and then repairing the damage. The repair process, which initially evolved to protect mammalian lungs from foreign matter and antigens, may however, produce further lung damage resulting in the impairment of gas exchange, the primary function of the lungs. Respiratory tract irritation often results in an inflammatory response involving the recruitment and activation of many cell types, mainly derived from the vascular system.</p> <p>Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by narcosis, reduced alertness, loss of reflexes, lack of coordination and vertigo.</p> <p>Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.</p> <p>Inhalation hazard is increased at higher temperatures.</p> <p>High inhaled concentrations of mixed hydrocarbons may produce narcosis characterised by nausea, vomiting and lightheadedness. Inhalation of aerosols may produce severe pulmonary oedema, pneumonitis and pulmonary haemorrhage.</p>
<b>Ingestion</b>	<p>Accidental ingestion of the material may be damaging to the health of the individual.</p> <p>Not normally a hazard due to physical form of product.</p> <p>Considered an unlikely route of entry in commercial/industrial environments</p> <p>Ingestion of petroleum hydrocarbons may produce irritation of the pharynx, oesophagus, stomach and small intestine with oedema and mucosal ulceration resulting; symptoms include a burning sensation in the mouth and throat. Large amounts may produce narcosis with nausea and vomiting, weakness or dizziness, slow and shallow respiration, swelling of the abdomen, unconsciousness and convulsions. Myocardial injury may produce arrhythmias, ventricular fibrillation and electrocardiographic changes. Central nervous system depression may also occur. Light aromatic hydrocarbons produce a warm, sharp, tingling sensation on contact with taste buds and may anaesthetise the tongue. Aspiration into the lungs may produce coughing, gagging and a chemical pneumonitis with pulmonary oedema and haemorrhage.</p>
<b>Skin Contact</b>	<p>Repeated exposure may cause skin cracking, flaking or drying following normal handling and use.</p> <p>Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.</p> <p>Limited evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a</p>



	<p>form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis.</p> <p>Spray mist may produce discomfort</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p> <p>The material may accentuate any pre-existing dermatitis condition</p> <p>Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects.</p>
<b>Eye</b>	<p>Evidence exists, or practical experience predicts, that the material may cause eye irritation in a substantial number of individuals and/or may produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals.</p> <p>Repeated or prolonged eye contact may cause inflammation characterised by temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.</p> <p>Direct contact with the eye may not cause irritation because of the extreme volatility of the gas; however concentrated atmospheres may produce irritation after brief exposures..</p> <p>Petroleum hydrocarbons may produce pain after direct contact with the eyes. Slight, but transient disturbances of the corneal epithelium may also result. The aromatic fraction may produce irritation and lachrymation.</p>
<b>Chronic</b>	<p>Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems.</p> <p>On the basis, primarily, of animal experiments, the material may be regarded as carcinogenic to humans. There is sufficient evidence to provide a strong presumption that human exposure to the material may result in cancer on the basis of:</p> <ul style="list-style-type: none"> <li>- appropriate long-term animal studies</li> <li>- other relevant information</li> </ul> <p>Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following.</p> <p>Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.</p> <p>Principal route of occupational exposure to the gas is by inhalation.</p> <p>Repeated or prolonged exposure to mixed hydrocarbons may produce narcosis with dizziness, weakness, irritability, concentration and/or memory loss, tremor in the fingers and tongue, vertigo, olfactory disorders, constriction of visual field, paraesthesias of the extremities, weight loss and anaemia and degenerative changes in the liver and kidney.</p> <p>Chronic exposure by petroleum workers, to the lighter hydrocarbons, has been associated with visual disturbances, damage to the central nervous system, peripheral neuropathies (including numbness and paraesthesias), psychological and neurophysiological deficits, bone marrow toxicities (including hypoplasia possibly due to benzene) and hepatic and renal involvement.</p>

<b>SW Kenyon Matt &amp; Semi Matt Dulling Spray</b>	<b>TOXICITY</b>	<b>IRRITATION</b>
	Not Available	Not Available
<b>LPG (liquefied petroleum gas)</b>	<b>TOXICITY</b>	<b>IRRITATION</b>
	Not Available	Not Available
<b>naphtha petroleum, light, hydrotreated, naphthenic</b>	<b>TOXICITY</b>	<b>IRRITATION</b>
	Not Available	Not Available
<b>methyl ethyl ketone</b>	<b>TOXICITY</b>	<b>IRRITATION</b>
	Dermal (rabbit) LD50: 20000 mg/kg	- mild
	Dermal (rabbit) LD50: 6480 mg/kg	Eye (human): 350 ppm -irritant
	Inhalation (rat) LC50: 50100 mg/m <sup>3</sup> /8 hr	Eye (rabbit): 80 mg - irritant
	Inhalation (rat) LD50: 23500 mg/m <sup>3</sup> /8 hr	Skin (rabbit): 402 mg/24 hr - mild
	Oral (rat) LD50: 2737 mg/kg	Skin (rabbit):13.78mg/24 hr open
	Not Available	Not Available
<b>n-hexane</b>	<b>TOXICITY</b>	<b>IRRITATION</b>
	Inhalation (rat) LD50: 48000 ppm/4h	Eye(rabbit): 10 mg - mild
	Oral (rat) LD50: 28710 mg/kg	
	Not Available	Not Available

Not available. Refer to individual constituents.

<b>LPG (LIQUEFIED PETROLEUM GAS)</b>	No significant acute toxicological data identified in literature search.
--------------------------------------	--



	<p>for Petroleum Hydrocarbon Gases:</p> <p>In many cases, there is more than one potentially toxic constituent in a refinery gas. In those cases, the constituent that is most toxic for a particular endpoint in an individual refinery stream is used to characterize the endpoint hazard for that stream. The hazard potential for each mammalian endpoint for each of the petroleum hydrocarbon gases is dependent upon each petroleum hydrocarbon gas constituent endpoint toxicity values (LC50, LOAEL, etc.) and the relative concentration of the constituent present in that gas. It should also be noted that for an individual petroleum hydrocarbon gas, the constituent characterizing toxicity may be different for different mammalian endpoints, again, being dependent upon the concentration of the different constituents in each, distinct petroleum hydrocarbon gas. All Hydrocarbon Gases Category members contain primarily hydrocarbons (i.e., alkanes and alkenes) and occasionally asphyxiant gases like hydrogen. The inorganic components of the petroleum hydrocarbon gases are less toxic than the C1 - C4 and C5 - C6 hydrocarbon components to both mammalian and aquatic organisms. Unlike other petroleum product categories (e.g. gasoline, diesel fuel, lubricating oils, etc.), the inorganic and hydrocarbon constituents of hydrocarbon gases can be evaluated for hazard individually to then predict the screening level hazard of the Category members</p>
<b>NAPHTHA PETROLEUM, LIGHT, HYDROTREATED, NAPHTHENIC</b>	No significant acute toxicological data identified in literature search.
<b>N-HEXANE</b>	The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

<b>Acute Toxicity</b>	Not Applicable	<b>Carcinogenicity</b>	Carcinogen Category 1B
<b>Skin Irritation/Corrosion</b>	Not Applicable	<b>Reproductivity</b>	Not Applicable
<b>Serious Eye Damage/Irritation</b>	Eye Irrit. 2	<b>STOT - Single Exposure</b>	STOT - SE (Resp. Irr.) Category 3 STOT - SE (Narcosis) Category 3
<b>Respiratory or Skin sensitisation</b>	Not Applicable	<b>STOT - Repeated Exposure</b>	Not Applicable
<b>Mutagenicity</b>	Not Applicable	<b>Aspiration Hazard</b>	Not Applicable

#### CMR STATUS

<b>CARCINOGEN</b>	LPG (liquefied petroleum gas)   Australia Exposure Standards - Carcinogens   Carc. 1B
-------------------	---

## SECTION 12 ECOLOGICAL INFORMATION

#### Toxicity

**DO NOT** discharge into sewer or waterways.

#### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
Not Available	Not Available	Not Available

#### Bioaccumulative potential

Ingredient	Bioaccumulation
Not Available	Not Available

#### Mobility in soil

Ingredient	Mobility
Not Available	Not Available

## SECTION 13 DISPOSAL CONSIDERATIONS

#### Waste treatment methods

<b>Product / Packaging disposal</b>	<ul style="list-style-type: none"> <li>▶ <b>DO NOT</b> allow wash water from cleaning or process equipment to enter drains.</li> <li>▶ It may be necessary to collect all wash water for treatment before disposal.</li> <li>▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li> <li>▶ Where in doubt contact the responsible authority.</li> <li>▶ Consult State Land Waste Management Authority for disposal.</li> <li>▶ Discharge contents of damaged aerosol cans at an approved site.</li> <li>▶ Allow small quantities to evaporate.</li> <li>▶ <b>DO NOT</b> incinerate or puncture aerosol cans.</li> </ul>
-------------------------------------	--

## SECTION 14 TRANSPORT INFORMATION

#### Labels Required

	
Marine Pollutant: NO	
HAZCHEM	2YE

#### Land transport (ADG)

UN number	1950
Packing group	Not Available
UN proper shipping name	AEROSOLS
Environmental hazard	No relevant data
Transport hazard class(es)	Class 2.1 Subrisk
Special precautions for user	Special provisions 63 190 277 327 limited quantity See SP 277

#### Air transport (ICAO-IATA / DGR)

UN number	1950
Packing group	Not Available
UN proper shipping name	Aerosols, flammable
Environmental hazard	No relevant data
Transport hazard class(es)	ICAO/IATA Class 2.1 ICAO / IATA Subrisk ERG Code 10L
Special precautions for user	Special provisions A145A167A802 Cargo Only Packing Instructions 203 Cargo Only Maximum Qty / Pack 150 kg Passenger and Cargo Packing Instructions 203 Passenger and Cargo Maximum Qty / Pack 75 kg Passenger and Cargo Limited Quantity Packing Instructions Y203 Passenger and Cargo Maximum Qty / Pack 30 kg G

#### Sea transport (IMDG-Code / GGVSee)

UN number	1950
Packing group	Not Available
UN proper shipping name	AEROSOLS
Environmental hazard	No relevant data
Transport hazard class(es)	IMDG Class 2.1 IMDG Subrisk
Special precautions for user	EMS Number F-D,S-U Special provisions 63 190 277 327 344 959 Limited Quantities SP277

#### Transport in bulk according to Annex II of MARPOL 73 / 78 and the IBC code

Source	Ingredient	Pollution Category	Residual Concentration - Outside Special Area (% w/w)	Residual Concentration
IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances	n-hexane	Not Available	Not Available	Not Available

### SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

<p><b>LPG (liquefied petroleum gas)(68476-85-7.) is found on the following regulatory lists</b></p>	<p>"Australia Hazardous Substances Information System - Consolidated Lists", "Australia - Queensland Work Health and Safety Regulation - Hazardous chemicals at major hazard facilities (and their threshold quantity)", "OECD List of High Production Volume (HPV) Chemicals", "Australia High Volume Industrial Chemical List (HVICL)", "International Chemical Secretariat (ChemSec) SIN List (*Substitute It Now!)", "Australia Work Health and Safety Regulations 2011 - Hazardous chemicals at major hazard facilities and their threshold quantity", "Australia Inventory of Chemical Substances (AICS)", "Australia - Tasmania - Work Health and Safety Regulations 2012 - Hazardous Chemicals at Major Hazard Facilities (and their Threshold Quantity) - Table 15.1", "Australia - New South Wales -Work Health and Safety Regulation 2011 - Hazardous chemicals", "Australia Exposure Standards", "International Maritime Dangerous Goods Requirements (IMDG Code) - Substance Index", "Australia - Victoria Occupational Health and Safety Regulations - Schedule 9: Materials at Major Hazard Facilities (And Their Threshold Quantity) Table 1", "Australia - South Australia - Work Health and Safety Regulations 2012 - Schedule 15—Hazardous chemicals at major hazard facilities (and their threshold quantity) Table 15.1", "Australia - New South Wales - Work Health and Safety Regulation 2011 - Hazardous chemicals at major hazard facilities (and their threshold quantity) - Table 15.1", "International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List Passenger and Cargo Aircraft", "Australia Dangerous Goods Code (ADG Code) - Packing Instruction - Liquefied and Dissolved Gases", "International Maritime Dangerous Goods Requirements (IMDG Code)", "Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes", "Belgium Federal Public Service Mobility and Transport, Regulations concerning the International Carriage of Dangerous Goods by Rail - Table A: Dangerous Goods List - RID 2013 (Dutch)", "International Air Transport Association (IATA) Dangerous Goods Regulations", "Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List"</p>
<p><b>naphtha petroleum, light, hydrotreated, naphthenic(92062-15-2) is found on the following regulatory lists</b></p>	<p>"Australia Hazardous Substances Information System - Consolidated Lists", "OECD List of High Production Volume (HPV) Chemicals", "International Council of Chemical Associations (ICCA) - High Production Volume List", "International Maritime Dangerous Goods Requirements (IMDG Code) - Substance Index", "International Maritime Dangerous Goods Requirements (IMDG Code)", "Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes", "Belgium Federal Public Service Mobility and Transport, Regulations concerning the International Carriage of Dangerous Goods by Rail - Table A: Dangerous Goods List - RID 2013 (Dutch)", "International Air Transport Association (IATA) Dangerous Goods Regulations", "Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5", "Australia FAISD Handbook - First Aid Instructions, Warning Statements, and General Safety Precautions", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2)"</p>
<p><b>methyl ethyl ketone(78-93-3) is found on the following regulatory lists</b></p>	<p>"Australia Illicit Drug Reagents/Essential Chemicals - Category III", "Australia Hazardous Substances Information System - Consolidated Lists", "OECD List of High Production Volume (HPV) Chemicals", "Australia High Volume Industrial Chemical List (HVICL)", "IOFI Global Reference List of Chemically Defined Substances", "International Fragrance Association (IFRA) Survey: Transparency List", "Australia National Pollutant Inventory", "Australia FAISD Handbook - First Aid Instructions, Warning Statements, and General Safety Precautions", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2)", "Australia Inventory of Chemical Substances (AICS)", "FisherTransport Information", "Sigma-AldrichTransport Information", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "IMO IBC Code Chapter 17: Summary of minimum requirements", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "Australia Customs (Prohibited Exports) Regulations 1958 - Schedule 9 Precursor substances - Part 2", "Australia Exposure Standards", "International Maritime Dangerous Goods Requirements (IMDG Code) - Substance Index", "International Maritime Dangerous Goods Requirements (IMDG Code)", "Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes", "Belgium Federal Public Service Mobility and Transport, Regulations concerning the International Carriage of Dangerous Goods by Rail - Table A: Dangerous Goods List - RID 2013 (Dutch)", "International Air Transport Association (IATA) Dangerous Goods Regulations", "Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List", "United Nations List of Precursors and Chemicals Frequently used in the Illicit Manufacture of Narcotic Drugs and Psychotropic Substances Under International Control (Red List) - Table II", "United Nations Convention Against Illicit Traffic in Narcotic Drugs and Psychotropic Substances - Table II", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix F (Part 3)", "OSPAR National List of Candidates for Substitution – Norway"</p>
<p><b>n-hexane(110-54-3) is found on the following regulatory lists</b></p>	<p>"Australia Hazardous Substances Information System - Consolidated Lists", "International Chemical Secretariat (ChemSec) SIN List (*Substitute It Now!)", "International Fragrance Association (IFRA) Survey: Transparency List", "Australia National Pollutant Inventory", "International Maritime Dangerous Goods Requirements (IMDG Code) - Substance Index", "FisherTransport Information", "Sigma-AldrichTransport Information", "IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances", "Australia Exposure Standards", "International Maritime Dangerous Goods Requirements (IMDG Code)", "Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes", "Belgium Federal Public Service Mobility and Transport, Regulations concerning the International Carriage of Dangerous Goods by Rail - Table A: Dangerous Goods List - RID 2013 (Dutch)", "International Air Transport Association (IATA) Dangerous Goods Regulations", "Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5", "Australia FAISD Handbook - First Aid Instructions, Warning Statements, and General Safety Precautions", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2)", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO Provisional Categorization of Liquid Substances - List 2: Pollutant only mixtures containing at least 99% by weight of components already assessed by IMO", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "OSPAR National List of Candidates for Substitution – Norway", "OECD List of High Production Volume (HPV) Chemicals", "Australia High Volume Industrial Chemical List (HVICL)", "International Council of Chemical Associations (ICCA) - High Production Volume List", "Australia Inventory of Chemical Substances (AICS)"</p>

## SECTION 16 OTHER INFORMATION

### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

[www.chemwatch.net/references](http://www.chemwatch.net/references)

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.